

Dependent Resurvey of a Portion of the South Boundary,
T. 19 S., R. 7 W., Willamette Meridian, Oregon

CHAINS 40.40	Dry creek bed, 4 lks. wide, course N.; asc. 5 ft. over NE. slope.
40.53	The cor. of secs. 31 and 32 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. <div style="text-align: center;"> T 19 S R 7 W S 31 S 32 T 20 S R 7 W S 5 1949 </div> from which bearing trees mkd. by Price and Tillman A fir, 45 ins. diam., bears N. $82\frac{3}{4}^{\circ}$ E., 71 lks. dist., with healed blaze. A fir, 27 ins. diam., bears N. $13\frac{1}{2}^{\circ}$ W., 91 lks. dist., with healed blaze. Set a 5 ft. steel fence post alongside iron post. Land, mountainous. Soil, rocky clay with sandstone outcroppings. Timber, fir, hemlock, cedar, maple, alder, chinquapin, madrone, and dogwood; undergrowth, vine maple, hazel, arrowwood, huckleberry, poison oak, Oregon grape, salal, and fern.
	N. $89^{\circ} 28'$ W., on the S. bdy. of sec. 31. Ascend 300 ft. over NE. slope, through heavy timber and dense undergrowth.
5.20	Spur, slopes N. 15° E.; desc. 110 ft. over NW. slope.
8.84	True point for the closing cor. of secs. 5 and 6, T. 20 S R. 7 W., hereinafter described. Descend 100 ft. over NW. slope.
11.10	Head of ravine, drains N. 40° W.; asc. 5 ft. over NE. slope.
11.80	Spur, slopes NW.; desc. 65 ft. over NW. slope.
13.80	Ravine, drains NE.; asc. 420 ft. over SE. slope, changing to steep E. slope.
22.20	Spur, slopes NE.; asc. 70 ft. along broken N. slope, changing to NE. slope.
25.50	Ridge, bears N. 10° W. and S. 10° E.; desc. 160 ft. over W. slope.
26.60	Gravelled road, 30 lks. wide, bears N. 5° E. and S. 5° E.
32.80	Creek, 2 lks. wide, course S. 20° W.; asc. 80 ft. over SE. slope.
38.09	The $\frac{1}{4}$ sec. cor. of sec. 31 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.