

339

Dependent Resurvey of a Portion of the South Boundary,
T. 19 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

$\frac{1}{4}$ S 31
1949

from which the remains of the original bearing trees

A fir snag, 27 ins. diam., bears N. 28° E., 18 lks. dist., with healed blaze.

✓ A sawed fir stump, 35 ins. diam., bears N. 30° W., 16 lks. dist., with healed blaze. (Record, 14 lks.)

and the remains of a bearing tree mkd. by Price and Tillman

✓ A sawed fir stump, 44 ins. diam., bears N. 29½° E., 53 lks. dist., with healed blaze.

and a new bearing tree

✓ A hemlock, 10 ins. diam., bears N. 74° W., 17 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

No other suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

S. 89° 09' W., beginning new measurement.

Ascend 70 ft. over SE. slope.

2.70 Spur, slopes S.; desc. 50 ft. over broken SW. slope.

11.10 Creek, 2 lks. wide, course S. 10° E.; asc. 110 ft. over SE. slope.

14.00 Gravelled road, 30 lks. wide, bears N. 10° E., curving E. and S. 5° E.

15.10 Intersect the E. bdy. of T. 19 S., R. 8 W.

The closing cor. of Tps. 19 and 20 S., R. 7 W., hereinbefore described.

From this point, the $\frac{1}{4}$ sec. cor. of sec. 36 only, T. 19 S., R. 8 W., bears N. 0° 10' E., 4.76 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay with sandstone outcroppings.

Timber, fir, hemlock, cedar, maple, alder, chinquapin, madrone, and dogwood; undergrowth, vine maple, hazel, arrowwood, poison oak, Oregon grape, salal, and fern.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Thomas E. Todd,
U. S. Deputy Surveyor, in 1891,
and the remonumentation by William W. Glenn and
Lynn M. Roseberry, Cadastral Surveyors, in 1966-67)

From the cor. of secs. 13, 14, 23, and 24, perpetuated

REC. 5286
1949
SURVEY FILED
MAR. 1981
M87-8
RECORDS
5286
D.R.