

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

## CHAINS

and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

T 20 S  
S 14 | S 13  
S 23 | S 24  
R 7 W  
1958

from which the remains of the original bearing trees

A decayed hemlock stump, size indeterminate, bears N. 47° E., 10 lks. dist., with fragmentary scribe marks visible on opened decayed blaze.

A fir, 58 ins. diam., bears S. 40° W., 35 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Byron

A sawed cedar stump, 36 ins. diam., bears N. 2½° E., 62 lks. dist., no marks visible.

A hemlock, 20 ins. diam., bears N. 18° W., 123½ lks. dist., with healed blaze.

and new bearing trees

A fir, 5 ins. diam., bears N. 62° E., 17 lks. dist., mkd. X BT.

A hemlock, 8 ins. diam., bears N. 21° W., 66 lks. dist., mkd. T20S R7W S14 BT.

No other suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

N. 0° 13' W., bet. secs. 13 and 14, marking and blazing the true line.

Ascend 295 ft. over SW. slope, through heavy second growth timber and dense undergrowth.

9.20 Spur, slopes S. 75° E.; desc. 170 ft. over N. slope.

16.10 Ravine, drains N. 80° E.; asc. 310 ft. over SE. slope.

34.90 Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E., also ridge, bears N. 60° W. and S. 80° E.; desc. 195 ft. over N. slope.

39.19 Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
¼  
S 14 | S 13  
1977

from which