

341

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

## CHAINS

A fir, 25 ins. diam., bears N. 6° E., 49 lks.  
dist., mkd. ½ S13 BT.

A fir, 28 ins. diam., bears S. 80° W., 60 lks.  
dist., mkd. ½ S14 BT.

Set a 5 ft. steel fence post alongside iron post.

Descend 90 ft. over N. slope.

40.80 Ravine, drains N. 50° E.; asc. 50 ft. over SE. slope.

45.30 Spur, slopes E.; desc. 40 ft. over NE. slope.

47.10 Bottom of descent, drains N. 85° E.; asc. 45 ft. over  
SE. slope.

49.90 Spur, slopes E.; desc. 105 ft. over NE. slope.

52.00 Ravine, drains N. 50° E.; asc. 60 ft. over SE. slope.

55.30 Spur, slopes N. 80° E.; desc. 60 ft. over NE. slope.

57.10 Ravine, drains S. 80° E.; asc. 135 ft. over SE. slope.

64.70 Spur, slopes N. 50° E.; desc. 440 ft. over NW. slope.

77.50 Dry creek bed, 3 lks. wide, course N. 60° E.; asc. 20  
ft. over SE. slope.

78.38 The cor. of secs. 11, 12, 13, and 14, monumented with the  
original sandstone, 20 x 18 x 8 ins., firmly set, 10  
ins. in the ground, mkd. X on top, with 4 notches on S.  
and 1 notch on E. edges, from which the remains of the  
original bearing trees:

A burned fir snag, 48 ins. diam., bears N. 38° E.,  
178 lks. dist., with scribe marks T20S R7W S BT  
visible on open blaze. (Record, N. 40° E.,  
125 lks.)

A burned fir snag, 45 ins. diam., bears S. 26° W.,  
150 lks. dist., with scribe marks 20S BT visible  
on burned open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 20 S R 7 W  
S 11 | S 12  
S 14 | S 13  
1977

from which new bearing trees

A fir, 35 ins. diam., bears N. 44° E., 56 lks.  
dist., mkd. T20S R7W S12 BT.

A fir, 19 ins. diam., bears S. 44° E., 38 lks.  
dist., mkd. T20S R7W S13 BT.

A fir, 40 ins. diam., bears S. 82½° W., 20 lks.  
dist., mkd. T20S R7W S14 BT.