

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	T 20 S R 7 W $\frac{1}{4}$ $\frac{S 12}{S 13}$ 1977
	from which  A fir, 20 ins. diam., bears N. $2\frac{1}{2}^{\circ}$ W., 42 lks. dist., mkd. $\frac{1}{4}$ S12 BT.  A fir, 33 ins. diam., bears S. $11\frac{1}{2}^{\circ}$ E., 70 lks. dist., mkd. $\frac{1}{4}$ S13 BT.  Set a 5 ft. steel fence post alongside iron post.  Descend 305 ft. over SW. slope.
52.10	Dry creek bed, 3 lks. wide, course N. $55^{\circ}$ W.; asc. 80 ft. over NE. slope.
56.00	Spur, slopes N. $60^{\circ}$ W.; desc. 205 ft. over SW. slope.
64.70	Dry bed of Haight Creek, 4 lks. wide, course N. $20^{\circ}$ W.; asc. 155 ft. over E. slope.
69.00	Spur, slopes NE.; desc. 90 ft. over NW. slope.
76.90	Dry creek bed, 4 lks. wide, course N. $70^{\circ}$ E.; asc. 50 ft. over SE. slope.
78.94	The cor. of secs. 11, 12, 13, and 14.  Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, yew, maple, alder, madrone, chinquapin, and dogwood; undergrowth, vine maple, hazel, arrowwood, huckleberry, poison oak, Oregon grape, salal, and fern.
	N. $0^{\circ} 30'$ W., bet. secs. 11 and 12.  Ascend 80 ft. over SE. slope, through heavy timber and dense undergrowth.
2.30	Spur, slopes S. $65^{\circ}$ E.; asc. 15 ft. along E. slope.
4.10	Ravine, drains S. $30^{\circ}$ E.; asc. 190 ft. over SE. slope.
8.90	Spur, slopes N. $60^{\circ}$ E.; desc. 415 ft. over NW. slope.
18.70	Ravine, drains N. $55^{\circ}$ E.; asc. 105 ft. over SE. slope.
22.90	Spur, slopes S. $80^{\circ}$ E.; desc. 170 ft. over NE. slope.
33.00	Haight Creek, 8 lks. wide, course N. $60^{\circ}$ W.; desc. 5 ft. along creek bottom.
34.20	Haight Creek, 8 lks. wide, course N. $30^{\circ}$ E.; desc. 5 ft. along creek bottom.
35.20	Haight Creek, 10 lks. wide, course N. $70^{\circ}$ W.; asc. 5 ft. along W. slope.
39.85	The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, determined from the remains of the original bearing trees: