

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

## CHAINS

A decayed fir stump, 40 ins. diam., bears  
N. 61° E., 38 lks. dist., no marks visible.

A decayed fir snag, 38 ins. diam., bears N. 83° W.,  
20 lks. dist., no marks visible on open decayed  
blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 20 S R 7 W

½  
S 11 | S 12  
1977

from which

A fir, 22 ins. diam., bears N. 69° E., 6 lks.  
dist., mkd. ½ S12 BT.

A fir, 28 ins. diam., bears S. 25° W., 43 lks.  
dist., mkd. ½ S11 BT.

Set a 5 ft. steel fence post alongside iron post.

N. 0° 25' W., beginning new measurement.

Ascend 10 ft. along W. slope.

- 7.30 Spur, slopes S. 75° W.; desc. 55 ft. over NW. slope.
- 12.00 Haight Creek, 6 lks. wide, course N. 40° E.; asc. 40 ft.  
along broken E. slope.
- 21.20 Top of ascent, slopes E.; desc. 50 ft. over NE. slope.
- 27.30 Dry creek bed, 2 lks. wide, course E.; asc. 45 ft. over  
SE. slope.
- 34.90 Top of ascent, slopes E.; desc. 85 ft. over NE. slope.
- 39.54 The cor. of secs. 1, 2, 11, and 12, determined from the  
remains of the original bearing trees:
- An alder snag, 15 ins. diam., bears N. 43° E., 30  
lks. dist., with fragmentary scribe marks visible  
on open decayed blaze.
- A root hole, bears S. 40° W., 27 lks. dist., with  
a down, burned, and broken cedar alongside, size  
indeterminate, no marks visible.
- An alder snag, 24 ins. diam., bears N. 60° W., 23  
lks. dist., with axe marks visible on open  
decayd blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins.  
in the ground, with brass cap mkd.

T 20 S R 7 W  
S 2 | S 1  
S 11 | S 12  
1977