

345

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

An alder, 20 ins. diam., bears N. 52° E., 34 lks.
dist., mkd. T20S R7W S1 BT.

A cedar, 32 ins. diam., bears S. 53° E., 71 lks.
dist., mkd. T20S R7W S12 BT.

A fir, 28 ins. diam., bears S. 88° W., 121 lks.
dist., mkd. T20S R7W S11 BT.

A cedar, 9 ins. diam., bears N. 61° W., 89 lks.
dist., mkd. T20S R7W S2 BT.

Set a 5 ft. steel fence post alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, maple, alder, madrone,
chinquapin, and dogwood; undergrowth, vine maple, hazel,
arrowwood, huckleberry, salmonberry, Oregon grape, salal,
and fern.

From the cor. of secs. 1 and 12 only, on the E. bdy. of
the Tp., monumented with an iron post, 2½ ins. diam.,
firmly set, mkd. and witnessed as described in the field
notes of the dependent resurvey of a portion of the E.
bdy. of T. 20 S., R. 7 W., executed concurrently under
this same Group.

N. 89° 44' W., bet. secs. 1 and 12.

Ascend 25 ft. over SE. slope, through heavy timber and
dense undergrowth.

2.30 Top of ascent, slopes S.; desc. 10 ft. along S. slope.

7.80 Ravine, drains S. 10° E.; asc. 230 ft. over E. slope.

17.80 Ridge, bears N. 15° E. and S. 15° W.; desc. 65 ft. over
W. slope.

18.60 Gravelled road, 30 lks. wide, bears N. 10° E. and S.,
in slight curve.

19.92 Point for the E 1/16 sec. cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

E 1/16 $\frac{S 1}{S 12}$
1977

from which

A fir, 10 ins. diam., bears N. 72° W., 13 lks.
dist., mkd. E 1/16 S1 BT.

A fir, 15 ins. diam., bears S. 82° W., 44 lks.
dist., mkd. E 1/16 S12 BT.

Set a 5 ft. steel fence post alongside iron post.

Descend 450 ft. over W. slope, changing to SW. slope.