

347

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 2 S 1 1977</p> <p>from which</p> <p>A fir, 12 ins. diam., bears N. 75½° E., 30 lks. dist., mkd. S 1/16 S1 BT.</p> <p>A fir, 16 ins. diam., bears N. 33° W., 8 lks. dist., mkd. S 1/16 S2 BT.</p> <p>Set a 5 ft. steel fence post alongside iron post.</p> <p>Ascend 65 ft. over broken SW. slope.</p>
37.68	<p>The ¼ sec. cor. of secs. 1 and 2, monumented with the original sandstone, 12 x 12 x 8 ins., firmly set 4 ins. in the ground, mkd. ¼ on W. face and X on top, from which the remains of the original bearing trees:</p> <p>A fir, 77 ins. diam., bears N. 70° E., 74 lks. dist., with healed blaze. (Record, N. 74° E., 94 lks.)</p> <p>A fir stump, 60 ins. diam., bears S. 83° W., 110 lks. dist., with a down fir alongside with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 7 W ¼ S 2 S 1 1977</p> <p>from which a new bearing tree</p> <p>A fir, 22 ins. diam., bears S. 43° W., 18 lks. dist., mkd. ¼ S2 BT.</p> <p>Deposit corner stone and set a 5 ft. steel fence post alongside iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 27' E., beginning new measurement.</p> <p>Ascend 130 ft. over broken SW. slope.</p>
10.20	Spur, slopes N. 70° W.; desc. 350 ft. over broken NW. slope.
20.60	Creek, 4 lks. wide, course S. 65° W.; asc. 520 ft. over S. slope.
21.00	Enter old logged area, edge bears E. and W.
46.70	Gravelled road, 25 lks. wide, bears N. 45° W. and S. 75° E., in curve.
48.50	Spur, slopes S. 20° W.; asc. 15 ft. along W. slope.