

349

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">T 19 S R 7 W ½ S 1 T 20 S R 7 W 1977</p> <p>from which</p> <p>A fir, 35 ins. diam., bears S. 3° E., 72 lks. dist., mkd. ½ S1 BT.</p> <p>A cedar, 22 ins. diam., bears S. 65½° W., 128 lks. dist., mkd. ½ S1 BT.</p> <p>Set a 5 ft. steel fence post alongside iron post.</p>
	<p>From the cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with the original sandstone, 16 x 8 x 4 ins., firmly set 16 ins. below surface of the ground, alongside iron rod, mkd. X on top, with 3 notches on S. and 2 notches on E. edges, from which bearing trees mkd. by Haines:</p> <p>A fir, 22 ins. diam., bears N. 83° E., 61½ lks. dist., with healed blaze.</p> <p>An alder, 24 ins. diam., bears S. 72° E., 48½ lks. dist., with scribe marks T20S R7W S23 BT visible on bark.</p> <p>A fir, 18 ins. diam., bears S. 2° W., 100 lks. dist., with healed blaze.</p> <p>A cedar, 14 ins. diam., bears N. 33° W., 65 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 7 W S 15 S 14 S 22 S 23 1977</p> <p>Deposit corner stone, reset iron rod, and set a 5 ft. steel fence post alongside iron post.</p> <p>N. 0° 47' W., bet. secs. 14 and 15.</p> <p>Descend 5 ft. along creek bottom, through heavy timber and dense undergrowth.</p>
2.60	Haney Creek, 8 lks. wide, course S. 60° W.; asc. slightly along creek bottom.
3.30	Haney Creek, 8 lks. wide, course S. 45° E.; asc. 35 ft. along broken W. slope.
6.40	Dirt road, 15 lks. wide, bears N. 15° W. and S. 15° E.
28.60	Creek, 6 lks. wide, course S. 35° W.; asc. 130 ft. over SE. slope.