

16114

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
31.30	Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.
35.50	Spur, slopes S. 60° E.; desc. 25 ft. over NE. slope.
38.10	Creek, 2 lks. wide, course S. 30° E.; asc. 25 ft. over SE. slope.
39.37	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T 20 S R 7 W $\frac{1}{4}$ S 15 S 14 1977 from which A fir, 25 ins. diam., bears S. 70° E., 7 lks. dist., mkd. $\frac{1}{4}$ S14 BT. A fir, 30 ins. diam., bears S. 59 $\frac{1}{2}$ ° W., 97 lks. dist., mkd. $\frac{1}{4}$ S15 BT. Set a 5 ft. steel fence post alongside iron post. Ascend 290 ft. over SE. slope.
47.90	Spur, slopes E.; desc. 195 ft. over NE. slope.
52.60	Creek, 1 lk. wide, course N. 60° E.; asc. 20 ft. over SE. slope.
53.60	Spur, slopes E.; desc. 15 ft. over NE. slope.
55.30	Creek, 2 lks. wide, course S. 40° E.; asc. 335 ft. over SW. slope.
66.60	Gravelled road, 20 lks. wide, bears E. and W., also enter Oxbow Burn, edge bears same as road.
68.10	Ridge, bears N. 80° E. and S. 65° W.; desc. 195 ft. over NW. slope.
78.74	The cor. of secs. 10, 11, 14, and 15, determined from the remains of the original bearing trees: A burned fir snag, 65 ins. diam., bears N. 89 $\frac{1}{2}$ ° E., 90 lks. dist., with scribe marks S R7W visible on opened blaze. (Record, 94 lks.) A sawed and burned fir stump, 28 ins. diam., bears S. 5° E., 137 lks. dist., no marks visible. A burned madrone snag, 8 ins. diam., bears S. 26° W., 18 lks. dist., with scribe marks S R visible on opened blaze. A burned fir snag, 50 ins. diam., bears N. 2° W., 9 lks. dist., with healed blaze. (Record, 13 lks.) At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.