

353

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">T 20 S R 7 W $\frac{1}{2}$ S 10 S 11 1977</p> <p>from which</p> <p>A sawed cedar stump, 36 ins. diam., bears S. 32° W., 67 lks. dist., mkd. $\frac{1}{2}$ S11 BT.</p> <p>No other suitable trees available within limits.</p> <p>Set a 5 ft. steel fence post alongside iron post.</p> <p>Corner falls in bottom of descent, slopes E.; asc. 40 ft. over SE. slope.</p>
43.00	Gravelled road, 20 lks. wide, on top of spur ridge, bears N. 5° W. and S. 15° W.; asc. 60 ft. over SE. slope.
57.60	Spur ridge, bears N. 65° W. and S. 30° W.; desc. 595 ft. over NE. slope.
61.20	Dirt road, 15 lks. wide, bears E. and W.
71.00	Ravine, drains N. 30° E.; asc. 5 ft. along E. slope.
74.50	Spur, slopes E.; desc. 65 ft. over NE. slope.
77.90	Creek, 4 lks. wide, course NW.; asc. 10 ft. over SW. slope.
78.72	<p>The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 7 W S 3 S 2 S 10 S 11 1967</p> <p>from which the remains of the original bearing trees</p> <p>A burned fir snag, 58 ins. diam., bears S. 64° W., 19 lks. dist., with scribe marks R7W S10 visible on opened blaze. (Record, S. 54° W.)</p> <p>A burned cedar snag, 22 ins. diam., bears N. 58° W., 10 lks. dist., with scribe marks T20S R7W S3 visible on open blaze. (Record, N. 69° W.)</p> <p>and a bearing tree mkd. by Glenn and Roseberry</p> <p>A maple, 31 ins. diam., bears N. 65° E., 243 lks. dist., with scribe marks T20S R7W S2 BT visible on open blaze. (Record, N. 62° E.)</p> <p>No other suitable trees available within limits.</p> <p>Set a 5 ft. steel fence post alongside iron post.</p> <p>Land, mountainous. Soil, rocky clay. Vegetation, young timber, vine maple, willow, hazel, arrowwood, manzanita, ceanothus, blackberry, Oregon grape, salal, and fern.</p>