

16118

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. 88° 33' W., bet. secs. 2 and 11.</p> <p>Ascend 385 ft. over NE. slope, through heavy timber and dense undergrowth.</p>
10.40	Spur ridge, bears N. and S.; desc. 305 ft. over steep W. slope.
18.40	Creek, 1 lk. wide, course N. 20° E.; asc. 30 ft. over SE. slope.
18.97	<p>Point for the E 1/16 sec. cor. of secs. 2 and 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 2}{S\ 11}$ 1977</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N. 19° E., 40 lks. dist., mkd. E 1/16 S2 BT.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 28° W., 37 lks. dist., mkd. E 1/16 S11 BT.</p> <p style="padding-left: 40px;">Set a 5 ft. steel fence post alongside iron post.</p> <p>Ascend 220 ft. over SE. slope.</p>
25.90	Spur, slopes N. 50° E.; asc. 10 ft. along N. slope.
28.30	Top of ascent, slopes N.; desc. 100 ft. over NW. slope.
35.90	Dry creek bed, 3 lks. wide, course N. 40° E.; asc. 130 ft. over SE. slope.
37.94	<p>The ¼ sec. cor. of secs. 2 and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, and a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 7 W ¼ $\frac{S\ 2}{S\ 11}$ 1967</p> <p>from which bearing trees mkd. by Glenn and Roseberry</p> <p style="padding-left: 40px;">A burned fir, 26 ins. diam., bears N. 23° E., 43 lks. dist., with scribe marks ¼ S2 BT visible on open blaze.</p> <p style="padding-left: 40px;">A burned cedar, 26 ins. diam., bears S. 3½° W., 48 lks. dist., with scribe marks ¼ S11 BT visible on open blaze. (Record, S. 59° W.)</p> <p style="text-align: center;">_____</p> <p>S. 89° 01' W., beginning new measurement.</p> <p>Ascend 275 ft. over SE. slope.</p>