

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
0.50	Spur, slopes NW.; desc. 220 ft. over N. slope.
7.70	Ravine, drains N. 75° W.; asc. 120 ft. over SW. slope.
19.60	Spur, slopes S. 80° W.; desc. 40 ft. over NW. slope.
22.50	Ravine, drains S. 85° W.; asc. 90 ft. over SW. slope.
30.10	Spur, slopes N. 70° W.; desc. 485 ft. over NW. slope.
43.90	Paved road, 35 lks. wide, bears N. 30° E. and S. 40° W., in curve, also enter timber, edge bears same as road.
46.00	Left bank Siuslaw River, bears N. 40° E. and S. 45° W., course S. 50° W.; thence across river.
47.50	Right bank Siuslaw River, bears N. 40° E. and S. 55° W.; asc. 50 ft. over SE. slope.
51.32	Intersect the S. bdy. of T. 19 S., R. 7 W.

True point for the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 19 S R 7 W
S 34
S 3 | S 2
T 20 S R 7 W
C C
1977

from which

A fir, 22 ins. diam., bears S. 66° E., 69 lks.
dist., mkd. T20S R7W S2 CC BT.

A fir, 23 ins. diam., bears S. 5° W., 87½ lks.
dist., mkd. T20S R7W S3 CC BT.

Set a 5 ft. steel fence post alongside iron post.

From this point, the original closing cor. of secs. 2 and
3, bears N. 0° 19' E., 0.21 chs. dist., monumented with
the original sandstone, 20 x 18 x 8 ins., firmly set 16
ins. in the ground, mkd. X on top, with 2 grooves on E.
and 4 grooves on W. faces, with an iron rod, 1½ ins.
diam., firmly set, projecting 14 ins. above ground,
alongside, from which the remains of the original bearing
trees:

A decayed fir stump, size indeterminate, bears
S. 12° E., 76 lks. dist., no marks visible.

A decayed fir stump, 44 ins. diam., bears
S. 15° W., 35 lks. dist., no marks visible.

A decayed fir stump, size indeterminate, bears
N. 20° W., 12¼ lks. dist., no marks visible.

and bearing trees mkd. by the County Surveyor (date
unknown)

A fir, 25 ins. diam., bears S. 10° E., 86 lks.
dist., with healed blaze.