

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
25.90	Spur, slopes N. 25° E.; desc. 50 ft. over NW. slope.
30.50	Ravine, drains N. 15° E.; asc. 90 ft. over E. slope.
34.70	Spur, slopes N. 30° E.; desc. 10 ft. along N. slope.
37.81	The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, perpetuated and recorded by Wiljo E. Green, Registered Land Surveyor No. 563, in 1967, for the Oregon State Board of Forestry, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	OREGON STATE BOARD OF FORESTRY $\frac{1}{4}$ <u>S 10</u> S 15 RS 563 1967
	from which the remains of the original bearing trees
	A fir snag, 56 ins. diam., bears N. 50 $\frac{1}{2}$ ° E., 17 lks. dist., with scribe marks $\frac{1}{4}$ S10 BT visible on open blaze. (Record, N. 40° E.)
	and the remains of a bearing tree mkd. by Green
	A sawed fir stump, 54 ins. diam., bears S. 73 $\frac{1}{2}$ ° E., 149 lks. dist., with scribe marks $\frac{1}{4}$ S15 BT visible on open blaze.
	No suitable trees available within limits.
	Set a 5 ft. steel fence post alongside iron post.
	Corner falls in head of ravine, drains N. 30° E.
	—————
	S. 89° 50' W., beginning new measurement.
	Ascend 60 ft. over E. slope.
2.00	Junction of gravelled roads, 25 lks. wide, bears S. 45° E., N. 45° W., and N. 25° W., on top of ridge, bears S. 45° E. and N. 25° W.; desc. 180 ft. over SW. slope.
19.75	The W $\frac{1}{16}$ sec. cor. of secs. 10 and 15, established by Wiljo E. Green, Registered Land Surveyor No. 563, in 1967, for the Oregon State Board of Forestry, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.
	OREGON STATE BOARD OF FORESTRY W $\frac{1}{16}$ <u>S 10</u> S 15 RS 563 1967
	from which the remains of bearing trees mkd. by Green
	A sawed and burned hemlock stump, 20 ins. diam., bears N. 10° E., 33 $\frac{1}{2}$ lks. dist., with scribe marks W $\frac{1}{16}$ S10 BT visible on open blaze.