

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	T 20 S R 7 W $\frac{1}{2}$ S 5   S 4 1977
	<p>No suitable trees available within limits.</p> <p>Set a 5 ft. steel fence post alongside iron post.</p> <p>N. 0° 12' W., bet. secs. 4 and 5.</p> <p>Ascend 120 ft. over S. slope, through dense undergrowth, across Oxbow Burn.</p>
5.30	Spur ridge, bears N. 70° E. and S. 70° W.; desc. 530 ft. over N. slope.
25.70	Creek, 2 lks. wide, course N. 80° E.; asc. 450 ft. over SE. slope.
35.50	Spur, slopes S. 35° E.; desc. 140 ft. over NE. slope.
44.70	Ravine, drains S. 40° E.; asc. 360 ft. over SW. slope.
52.50	Gravelled road, 15 lks. wide, bears S. 85° E. and N. 85° W.
54.70	Spur, slopes S. 35° E.; desc. 5 ft. over NE. slope.
56.24	Intersect the S. bdy. of T. 19 S., R. 7 W.
	<p>True point for the closing cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	T 19 S R 7 W S 32 S 5   S 4 T 20 S R 7 W C C 1977
	<p>from which</p> <p>A fir, 6 ins. diam., bears S. 31½° E., 15 lks. dist., mkd. T20S R7W S4 CC BT.</p> <p>A fir, 7 ins. diam., bears S. 62° W., 10 lks. dist., mkd. T20S R7W S5 CC BT.</p> <p>Set a 5 ft. steel fence post alongside iron post.</p> <p>From this point, the original closing cor. of secs. 4 and 5, bears N. 0° 12' W., 0.02 chs. dist., monumented with an iron rod, 1 in. diam., firmly set, projecting 20 ins. above ground, from which the remains of the original bearing trees:</p> <p>A sawed fir stump, 48 ins. diam., bears N. 24° E., 22 lks. dist., with axe marks visible on opened and burned blaze.</p> <p>A root hole, bears S. 8° W., 43 lks. dist., with a down fir alongside, 54 ins. diam., no marks visible.</p>