

363

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 24 ins. diam., bears N. 72° W., 58½ lks. dist., mkd. 80 1/16 S6 BT.

Set a 5 ft. steel fence post alongside iron post.

From this point, a local point established by person(s) unknown, bears S. 73¾° E., 0.08 chs. dist., monumented with a fir post, 2 ins. diam., loosely set, 4 ins. in the ground, from which locally mkd. bearing trees:

A maple, 18 ins. diam., bears N. 72° E., 15 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir, 20 ins. diam., bears N. 62° W., 48½ lks. dist., with illegible scribe marks visible on partially healed blaze.

Ascend 275 ft. over S. slope.

44.90 Gravelled road, 30 lks. wide, bears N. 45° W. and S. 65° E., in curve.

47.80 Ridge, bears S. 50° E. and W.; desc. 315 ft. over NW. slope.

57.02 Intersect the S. bdy. of T. 19 S., R. 7 W.

True point for the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 19 S R 7 W
S 31
S 6 | S 5
T 20 S R 7 W
C C
1977

from which

A fir, 33 ins. diam., bears S. 41° E., 74 lks. dist., mkd. T20S R7W S5 CC BT.

A fir, 15 ins. diam., bears S. 36° W., 85 lks. dist., mkd. T20S R7W S6 CC BT.

Set a 5 ft. steel fence post alongside iron post.

From this point, the original closing cor. of secs. 5 and 6, bears N. 0° 01' E., 0.11 chs. dist., monumented with the original sandstone, 24 x 16 x 12 ins., firmly set, 12 ins. in the ground, mkd. X on top, with 5 grooves on E. and 1 groove on W. faces, and CC on N. face, and with an iron rod, ¾ in. diam., firmly set, projecting 10 ins. above ground, alongside, from which the remains of the original bearing trees:

A fir snag, 50 ins. diam., bears N. 28° E., 98 lks. dist., with healed blaze.

A decayed fir stump, size indeterminate, bears S. 78° E., 21 lks. dist., no marks visible.

and bearing trees mkd. by the County Surveyor (date unknown)