

Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Harvey Gordon and Charles T. Gardner, U. S. Deputy Surveyors, in 1855, and the survey by Carl S. Nicklin and Winfield S. Chapman, U. S. Deputy Surveyors, in 1897)

Beginning at the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, perpetuated and recorded by Milo Godfrey, Deputy County Surveyor in 1963, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 23 S
 $\frac{1}{4}$ S 35 R
S 2 4
T 24 S W
1963

from which the remains of the original bearing trees

A fir snag, 48 ins. diam., bears S. 82° W., 28 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on opened blaze. Rescribed by Godfrey, in 1963, with scribe marks $\frac{1}{4}$ S35 CS BT visible on open blaze, alongside original blaze.

and the remains of a bearing tree mkd. by Godfrey

A fir snag, 18 ins. diam., bears West, 252 lks. dist., with healed blaze.

and a bearing object of which I have no record

A basalt stone, 3 x 3 x 3 ft. above ground, bears N. $81\frac{1}{2}^\circ$ W., $28\frac{1}{2}$ lks. dist., with chisel marks XBO visible on top.

and a new bearing object

A conglomerate boulder, 8 x 6 x 4 ft. above ground, bears S. $28\frac{1}{2}^\circ$ E., 65 lks. dist., mkd. XBO on top.

S. $89^\circ 59'$ W., along the S. bdy. of sec. 35, marking and blazing the true line.

Descend 525 ft. over broken SW. slope, through scattered timber and dense undergrowth.

- 10.45 Spur, slopes S. 45° W.; desc. 390 ft. over broken W. slope.
- 23.30 Dirt road, 40 lks. wide, bears N. 50° W. and S. 35° E.
- 23.40 Head of ravine, drains S. 80° W.; desc. 30 ft. over broken SW. slope.
- 32.45 Ravine, drains S. 45° W.; asc. 75 ft. over SE. slope.
- 34.10 Dirt road, 40 lks. wide, bears N. 45° E. and S. 45° W.
- 39.06 Point for the closing cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. .
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.