

Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

T 23 S R 4 W
C | C
S 34 | S 35
S 2
T 24 S R 4 W
1976

from which

A fir, 8 ins. diam., bears N. 10° E., $35\frac{1}{2}$ lks.
dist., mkd. T23S R4W S35 CC BT.

A fir, 6 ins. diam., bears N. $58\frac{1}{2}^{\circ}$ W., 40 lks.
dist., mkd. T23S R4W S34 CC BT.

Descend 2 ft. over SW. slope.

From this point, the cor. of secs. 2 and 3 only, T 24 S.,
R. 4 W., bears S. $89^{\circ} 59'$ W., 0.96 chs. dist., perpetu-
ated and recorded by Milo Godfrey, Deputy County Surveyor
in 1962, and further perpetuated by Godfrey, in 1963,
monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set,
projecting 8 ins. above ground, with brass cap mkd.

T 24 S
S 3 | S 2
R 4 W
1962

from which the remains of bearing trees mkd. by Nicklin
and Chapman

A fir stump, 48 ins. diam., bears S. $33\frac{1}{2}^{\circ}$ E., 83
lks. dist., no marks visible on decayed blaze.
(Record, S. 32° E., 86 lks.)

A sawed fir stump, 30 ins. diam., bears S. 81° W.,
79 lks. dist., with healed blaze.

A madrone, 24 ins. diam., bears N. 64° W., 36 lks.
dist., with chaining notch visible on lower
portion of decayed blaze.

and the remains of bearing trees mkd. by Godfrey, in 1962

A fir, 18 ins. diam., bears S. 67° E., 57 lks.
dist., with scribe marks 4S R4 visible on
partially healed blaze.

A fir snag, 20 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ W., $64\frac{1}{2}$
lks. dist., with scribe marks T24S R4W S3 CS BT
visible on open blaze.

and a bearing tree mkd. by Godfrey, in 1963

A fir, 24 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ W., 133 lks.
dist., with healed blaze.

From this point, a 1 in. "T" shaped iron rod, firmly set,
projecting 8 ins. above ground, bears N. $2\frac{1}{2}^{\circ}$ W., 0.070
chs. dist.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, chinquapin,
alder, and myrtle; undergrowth, salal, rhododendron,
poison oak, vine maple, Oregon grape, hazel, and fern.

From the cor. of secs. 33 and 34 only, perpetuated by
Wilford N. Haines, Registered Land Surveyor No. 239, date
unknown, further perpetuated by James W. Byron, Deputy
County Surveyor, in 1959, and further perpetuated by Milo
E. Godfrey, Deputy County Surveyor, in 1963, monumented
with a 1 in. "T" shaped iron rod, firmly set, projecting
12 ins. above ground, from which the remaining original
bearing tree: