

4

Dependent Resurvey of a Portion of the South Boundary,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A maple, 36 ins. diam., bears S. 67° W., 58 lks. dist., with scribe marks R4W visible on partially open blaze.

and a bearing tree mkd. by Byron

A hemlock, 12 ins. diam., bears N. 29½° W., 8 lks. dist., with scribe marks S33 visible on partially open blaze.

and a bearing tree mkd. by Godfrey

A hemlock, 13 ins. diam., bears N. 39° E., 72½ lks. dist., with scribe marks R4W S34 visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

*FO 1195*  
*M121-69*

T 23 S R 4 W  
S 33 | S 34  
S 3  
T 24 S R 4 W  
1976

Reset iron rod alongside iron post.

S. 89° 58' W., along the S. bdy. of sec. 33.

Descend 5 ft. over NW. slope, through heavy timber and dense undergrowth.

1.25 Creek, 1 lk. wide, course N. 45° E.; asc. 40 ft. over SW. slope.

2.97 From this point, the closing cor. of secs. 3 and 4, T. 24 S., R. 4 W., bears North, 0.055 chs. dist., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, and further perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 23 S R 4 W  
CC S 33  
S 4 | S 3  
T 24 S  
1959

from which the remains of the original bearing trees

A root hole, bears S. 36° E., 35 lks. dist., with a turned out sawed fir stump alongside, 32 ins. diam., with healed blaze.

A fir, 44 ins. diam., bears S. 1° W., 28 lks. dist., no marks visible on open blaze.

and the remains of a bearing tree mkd. by Byron

A cedar snag, 8 ins. diam., bears S. 43° W., 52½ lks. dist., with fragmentary scribe marks visible on partially open blaze.

and a bearing tree mkd. by Godfrey

A cedar, 18 ins. diam., bears S. 69° E., 94 lks. dist., with fragmentary scribe marks visible on partially open blaze.

Ascend 455 ft. over broken E. slope.

22.15 Spur, slopes N. 35° E.; desc. 85 ft. over NW. slope.

29.45 Ravine, drains N. 40° E.; asc. 200 ft. over NE. slope.

38.90 Spur, slopes N. 35° E.; desc. 80 ft. over NW. slope.

40.68 Point for the ¼ sec. cor. of sec. 33 only, at proportionate distance; there is no remaining evidence of the original corner.