

16133

262

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears S. 47° W., 43 lks. dist., with
a down fir alongside, 18 ins. diam., no marks
visible.

A sawed fir stump, 60 ins. diam., bears N. 24° W.,
10 lks. dist., with axe marks visible on decayed
blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

FD 1/95
M121-69

¼
S 34 | S 35
T 23 S R 4 W
1976

from which new bearing trees

A fir, 6 ins. diam., bears S. 73½° E., 13 lks.
dist., mkd. ¼ S35 BT.

A fir, 8 ins. diam., bears S. 36½° W., 9½ lks.
dist., mkd. ¼ S34 BT.

S. 0° 18' W., beginning new measurement.

Ascend 25 ft. over NW. slope.

- 1.10 Spur, slopes S. 75° W.; desc. 85 ft. over SE. slope.
- 4.00 Ravine, drains W.; asc. 45 ft. over NW. slope.
- 5.45 Spur, slopes N. 70° W.; desc. 65 ft. over SW. slope.
- 9.30 Creek, 2 lks. wide, course N. 60° W.; asc. 150 ft. over
NW. slope.
- 15.30 Ridge, bears N. 70° W. and S. 70° E.; desc. 150 ft. over
SW. slope.
- 21.48 The witness cor. of secs. 34 and 35, determined from the
remains of the original bearing trees:

A root hole, bears S. 70° E., 18 lks. dist.

A sawed cedar stump, 25 ins. diam., bears S. 87° W.,
40½ lks. dist., with scribe marks BT visible on
opened blaze. (No distance indicated in the
record of the Wright survey.)

This corner became an angle point on line at the time of
the completion survey by Nicklin and Chapman, in 1897.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

A P
T 23 S R 4 W
S 34 | S 35
1976

from which new bearing trees