

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A hemlock, 20 ins. diam., bears N. 12½° E., 67 lks. dist., with healed blaze.</p> <p>A hemlock, 10 ins. diam., bears S. 63½° E., 96 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>A hemlock, 12 ins. diam., bears N. 36½° W., 34½ lks. dist., with scribe marks T23S R S CS BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W S 22 S 23 S 27 S 26 1976</p> <p>from which a new bearing tree</p> <p>A fir, 8 ins. diam., bears S. 59° W., 122½ lks. dist., mkd. T23S R4W S27 BT.</p> <p>Reset "T" shaped iron rod alongside iron post.</p> <p>N. 0° 14' W., bet. secs. 22 and 23.</p> <p>Ascend 2 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
0.60	Spur, slopes N. 80° E.; desc. 55 ft. over broken NE. slope.
5.05	Ravine, drains N. 40° E.; asc. 10 ft. over SE. slope.
7.05	Ridge, bears N. 55° E. and S. 55° W.; desc. 410 ft. over NW. slope.
22.60	Creek, 2 lks. wide, course N. 70° E.; asc. 10 ft. over SE. slope.
24.15	Spur, slopes N. 85° E.; desc. 40 ft. over NE. slope.
25.90	Creek, 10 lks. wide, course N. 85° W.; asc. 50 ft. over SW. slope.
30.30	Spur, slopes N. 85° W.; desc. 45 ft. over NW. slope.
34.90	Creek, 2 lks. wide, course N. 85° W.; asc. 90 ft. over SW. slope.
39.58	<p>The ¼ sec. cor. of secs. 22 and 23, perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1965, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees:</p> <p>A fir snag, 21 ins. diam., bears N. 20° E., 45 lks. dist., with scribe marks ¼ S visible on open blaze.</p> <p>and the remains of bearing trees mkd. by Tracy</p>