

16140

266

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir snag, 15 ins. diam., bears N. 38½° E., 79 lks. dist., with scribe marks ¼ S23 CS BT visible on open blaze.</p> <p>A grand fir, 14 ins. diam., bears S. 63° W., 30½ lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> ½ S 22 S 23 T 23 S R 4 W 1976 </p>
	<p>from which a new bearing tree</p> <p>A fir, 5 ins. diam., bears S. 85½° E., 70½ lks. dist., mkd. ¼ S23 BT.</p> <p>Reset "T" shaped iron rod alongside iron post.</p>
	<p>N. 0° 25' E., beginning new measurement.</p> <p>Descend 5 ft. over NW. slope.</p>
1.50	Bottom of descent, slopes W.; asc. 435 ft. over NE. slope.
28.35	Ridge, bears N. 60° E. and S. 75° W.; desc. 35 ft. over NW. slope.
29.60	Bottom of descent, slopes W.; asc. 30 ft. over SW. slope.
32.05	Spur, slopes N. 70° W.; desc. 155 ft. over NW. slope.
35.05	Ravine, drains N. 85° W.; asc. 70 ft. over SW. slope.
39.00	Spur, slopes N. 70° W.; desc. 45 ft. over NW. slope.
40.48	<p>The cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by Milo Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;"> T 23 S S 15 S 14 S 22 S 23 R 4 W 1963 </p>
	<p>from which the remains of the original bearing trees</p> <p>A root hole, bears N. 21° E., 15 lks. dist., with a down fir alongside, 24 ins. diam., with scribe marks 14 visible on opened blaze.</p> <p>and bearing trees mkd. by Godfrey</p> <p>A fir, 15 ins. diam., bears N. 54½° E., 33 lks. dist., with healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 61½° E., 15½ lks. dist., with healed blaze.</p>

*Fd. 7/90
Milo
CS 63/104*

*Fd. 4/90
C.S. 63/127*