

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
2.00	Ravine, drains S. 80° W.; asc. 130 ft. over SW. slope.
6.75	Gravelled road, 30 lks. wide, bears N. 85° E. and S. 85° W.
7.20	Ridge, bears N. 75° E. and S. 75° W.; desc. 280 ft. over NW. slope.
15.30	Ravine, drains N. 75° W.; asc. 105 ft. over SW. slope.
19.925	Point for the S 1/16 sec. cor. of secs. 14 and 15. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  S 1/16 S 15   S 14 1976  from which  A fir, 5 ins. diam., bears S. 28½° E., 14 lks. dist., mkd. S 1/16 S14 BT.  A fir, 4 ins. diam., bears S. 87° W., 11 lks. dist., mkd. S 1/16 S15 BT.  Ascend 5 ft. over broken SW. slope.
24.20	Ridge, bears N. 60° W. and S. 60° E.; desc. 165 ft. over NW. slope.
39.85	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  ¼ S 15   S 14 T 23 S R 4 W 1976  from which  A fir, 4 ins. diam., bears S. 10° E., 15 lks. dist., mkd. ¼ S14 BT.  A fir, 5 ins. diam., bears S. 21½° W., 21½ lks. dist., mkd. ¼ S15 BT.  Descend 210 ft. over broken NE. slope.
79.70	The cor. of secs. 10, 11, 14, and 15, determined from the remains of the original bearing trees:  A white oak, 31 ins. diam., bears N. 2° E., 68 lks. dist., with healed blaze.  and bearing trees and a reference monument mkd. and recorded by Wilford Haines, Registered Land Surveyor No. 239, in 1961  An oak, 38 ins. diam., bears S. 85½° E., 142 lks. dist., with healed blaze.