

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
20.10	Bottom of descent, slopes E.; asc. 10 ft. over SE. slope.
21.05	Spur, slopes N. 70° E.; desc. 180 ft. over broken NE. slope.
30.05	Elk Creek, 20 lks. wide, course S. 35° W., curving to N.; asc. 10 ft. over SE. slope, along creek bottom.
33.00	Elk Creek, 20 lks. wide, course N. 20° E., curving N.; continue along creek bottom.
33.60	Elk Creek, 20 lks. wide, course N. 15° E. from S. 10° E.; asc. slightly along creek bottom.
36.00	Top of ascent, slopes E.; desc. 2 ft. over N. slope.
40.04	The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, perpetuated and recorded by Wilford Haines, Registered Land Surveyor No. 239, in 1960, and further perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1965, from original evidence no longer in existence, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, with brass capped top 2 ins. below surface of gravelled driveway, 15 lks. wide, bears N. and S., turning SW. The brass cap is mkd.
	<p>FD. OK 9/9*</p> <p>BY BAKER M119-38</p> <p>T 23 S</p> <p>$\frac{1}{4}$ S 33 S 34</p> <p>R 4 W</p> <p>1965</p> <p>from which bearing trees mkd. by Tracy</p> <p>A grand fir, 10 ins. diam., bears S. 41° E., 120$\frac{1}{2}$ lks. dist., with healed blaze.</p> <p>A cedar, 15 ins. diam., bears N. 73$\frac{1}{2}$° W., 193 lks. dist., with healed blaze.</p> <p>I add a reference monument</p> <p>An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 34° E., 28 lks. dist., with brass cap mkd. $\frac{1}{4}$ S34 RM 1976, and an arrow pointing to the corner.</p> <p>N. 1° 41' W., beginning new measurement.</p> <p>Ascend 10 ft. over S. slope, along E. track of driveway.</p>
10.35	Elk Creek, in culvert; 20 lks. wide, course W.; asc. slightly over S. slope.
13.90	Top of ascent, slopes W.; desc. 15 ft. over NW. slope.
15.70	Intersection of driveway with gravelled road, 20 lks. wide, bears N. 20° W. and S. 25° E.
16.50	Gravelled road, 20 lks. wide, bears N. 80° W. and S. 80° E.
26.65	Top of ascent, slopes W.; desc. 75 ft. over N. slope.
38.50	Creek, 3 lks. wide, course S. 60° W.; asc. 30 ft. over SW. slope.
40.26	Point for the cor. of secs. 27, 28, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.

SEE ALSO
THEIR'S BOOK
5 PG 1