

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS					
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>Ed 9/90 M110-58 FD 1/95 M121-69</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 S R 4 W</td> </tr> <tr> <td>S 28 S 27</td> </tr> <tr> <td>S 33 S 34</td> </tr> <tr> <td>1976</td> </tr> </table> <p>from which</p> <p>A fir, 18 ins. diam., bears N. 69½° E., 25 lks. dist., mkd. T23S R4W S27 BT.</p> <p>A fir, 8 ins. diam., bears S. 9½° E., 36 lks. dist., mkd. T23S R4W S34 BT.</p> <p>A fir, 5 ins. diam., bears S. 27° W., 40½ lks. dist., mkd. T23S R4W S33 BT.</p> <p>A fir, 10 ins. diam., bears N. 44½° W., 24 lks. dist., mkd. T23S R4W S28 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, oak, madrone, alder, myrtle, cedar, and chinquapin; undergrowth, salal, hazel, Oregon grape, rhododendron, poison oak, vine maple, and fern.</p>	T 23 S R 4 W	S 28 S 27	S 33 S 34	1976
T 23 S R 4 W					
S 28 S 27					
S 33 S 34					
1976					
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 89° 59' W., bet. secs. 27 and 34.</p> <p>Descend 130 ft. over broken SW. slope.</p>				
3.50	Dirt road, 15 lks. wide, bears N. 40° E. and S. 50° W.				
7.95	Creek, 2 lks. wide, course S. 55° W.; asc. 70 ft. over SE. slope.				
15.00	Spur, slopes S. 5° E.; desc. 60 ft. over SW. slope.				
19.20	Ravine, drains S.; asc. 75 ft. over SE. slope.				
22.60	Spur, slopes S. 25° E.; desc. 20 ft. over SW. slope.				
25.00	Bottom of descent, slopes S.; asc. 75 ft. over SE. slope.				
29.75	Ridge, bears N. 25° E. and S. 25° W.; desc. 115 ft. over NW. slope.				
33.80	Ravine, drains N. 20° W.; asc. 85 ft. over NE. slope.				
39.45	Top of ascent, slopes N.; desc. 15 ft. over NW. slope.				
40.39	<p>The ¼ sec. cor. of secs. 27 and 34, perpetuated and recorded by Wilford Haines, Registered Land Surveyor No. 239, in 1959, from original evidence no longer in existence, and further perpetuated by James W. Byron, County Surveyor, in 1960, and further perpetuated by Vernon Tracy, Deputy County Surveyor, in 1965, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 10 ins. above ground, from which the remains of a bearing tree mkd. by Haines:</p> <p>A fir stump, 8 ins. diam., bears N. 55½° E., 32 lks. dist., with fragmentary scribe marks visible on open blaze.</p>				