

279

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree of which I have no record

A madrone, 6 ins. diam., bears S. 88° W., 32 lks.
dist., with a nail with "W" embossed on head,
at base.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

¼ S 28
S 33
T 23 S R 4 W
1976

*Fd 9/90
M 110-58*

Reset "T" shaped iron rod alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, alder, myrtle, oak,
maple, and chinquapin; undergrowth, rhododendron, salal,
hazel, vine maple, poison oak, Oregon grape, and fern.

From the ¼ sec. cor. of secs. 20 and 21, perpetuated and
recorded by Wilford Haines, Registered Land Surveyor No.
239, in 1956, and further perpetuated by Vernon Tracy,
Deputy County Surveyor, in 1965, monumented with a 1 in.
"T" shaped iron rod, firmly set, projecting 10 ins.
above ground, with an aluminum washer mkd. RLS 239, from
which the remains of the original bearing trees:

A sawed fir stump, 28 ins. diam., bears S. 22° E.,
25 lks. dist., with scribe marks BT visible on
open blaze. (Record, S. 25° E.)

and bearing trees mkd. by Tracy

A fir, 10 ins. diam., bears S. 69¼° E., 28 lks.
dist., with healed blaze.

A fir, 9 ins. diam., bears S. 24½° W., 6 lks.
dist., with healed blaze.

and a bearing tree of which I have no record

A fir, 30 ins. diam., bears S. 68½° W., 90 lks.
dist., with scribe marks ¼ S20 T23S R4W BT
visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

¼
S 20 | S 21
T 23 S R 4 W
1976

Reset "T" shaped iron rod alongside iron post.

N. 0° 27' W., bet. secs. 20 and 21.

Descend 5 ft. over NE. slope, through heavy timber and
dense undergrowth.