

16154

200

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
0.10	Creek, 3 lks. wide, course N. 85° E.; asc. 10 ft. over SE. slope.
1.95	Top of ascent, slopes E.; desc. 40 ft. over NE. slope.
5.55	Creek, 3 lks. wide, course E.; asc. 240 ft. over SE. slope.
15.90	Ridge, bears E. and W.; desc. 50 ft. over NE. slope.
19.935	Point for the N 1/16 sec. cor. of secs. 20 and 21. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  N 1/16 S 20   S 21 1976  from which  A fir, 10 ins. diam., bears N. 64½° E., 20 lks. dist., mkd. N 1/16 S21 BT.  A fir, 11 ins. diam., bears N. 24½° W., 9½ lks. dist., mkd. N 1/16 S20 BT.  From this point, a 1 in. "T" shaped iron rod, firmly set, projecting 10 ins. above ground, bears S. 73¾° E., 0.050 chs. dist., from which locally mkd. bearing trees:  A fir, 8 ins. diam., bears S. 34½° E., 9 lks. dist., with healed blaze.  A fir, 6 ins. diam., bears S. 44° W., 6 lks. dist., with healed blaze.  Descend 135 ft. over NE. slope.
25.75	Creek, 2 lks. wide, course S. 80° E.; asc. 190 ft. over SE. slope.
39.87	Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T 23 S R 4 W S 17   S 16 S 20   S 21 1976  from which  A madrone, 8 ins. diam., bears N. 75° E., 84 lks. dist., mkd. T23S R4W S16 BT on bark.  A fir, 7 ins. diam., bears S. 74½° E., 60½ lks. dist., mkd. T23S R4W S21 BT.  From this point, a 1 in. "T" shaped iron rod, firmly set, projecting 10 ins. above ground, bears S. 52° E., 0.130 chs. dist., from which locally mkd. bearing trees: