

16156

202

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS
39.87

Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 17 | S 16
T 23 S R 4 W
1976

from which

A fir, 14 ins. diam., bears S. $14\frac{3}{4}^{\circ}$ E., 25 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

A fir, 13 ins. diam., bears N. $40\frac{1}{2}^{\circ}$ W., $20\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S17 BT.

Ascend 35 ft. over SE. slope.

42.15 Top of ascent, slopes E.; desc. 235 ft. over broken NE. slope.

68.70 Creek, 3 lks. wide, course N. 80° E.; asc. 175 ft. over SE. slope.

79.74 The cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by Arthur Boyer, Deputy County Surveyor, in 1938, from original evidence no longer in existence, further perpetuated by James W. Byron, Deputy County Surveyor, in 1957, and further perpetuated by Milo Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 23 S
S 8 | S 9
S 17 | S 16
R 4 W
1958

from which the remains of bearing trees mkd. by Boyer

A sawed fir stump, 30 ins. diam., bears S. $78\frac{1}{2}^{\circ}$ E., 97 lks. dist., with fragmentary scribe marks visible on bark blaze.

A sawed fir stump, 26 ins. diam., bears S. 3° W., 48 lks. dist., no marks visible on decayed blaze.

A fir, 25 ins. diam., bears N. $20\frac{1}{2}^{\circ}$ W., $72\frac{1}{2}$ lks. dist., with fragmentary scribe marks visible on bark blaze.

and bearing trees mkd. by Byron

A fir, 15 ins. diam., bears N. 77° E., 62 lks. dist., with healed blaze.

A cedar, 18 ins. diam., bears S. $66\frac{3}{4}^{\circ}$ E., 168 lks. dist., with healed blaze.

and a bearing tree mkd. by Godfrey