

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

W 1/16 S 29
S 32
1976

from which

A cedar, 30 ins. diam., bears N. 15½° E., 81 lks. dist., mkd. W 1/16 S29 BT.

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 39° E., 65½ lks. dist., with brass cap mkd. W 1/16 S32 RM 1976, and an arrow pointing to the corner.

Ascend 35 ft. over SE. slope.

63.45 Ridge, bears N. 40° E. and S. 40° W.; desc. 280 ft. over NW. slope.

74.35 Gravelled road, 30 lks. wide, bears N. 35° E. and S. 35° W.

79.96 Point for the cor. of secs. 29, 30, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 4 W
S 30 | S 29
S 31 | S 32
1976

from which

A fir, 5 ins. diam., bears N. 68½° E., 97 lks. dist., mkd. T23S R4W S29 BT.

A fir, 6 ins. diam., bears S. 53½° E., 61 lks. dist., mkd. T23S R4W S32 BT.

A cedar, 5 ins. diam., bears S. 85½° W., 39½ lks. dist., mkd. T23S R4W S31 BT.

No other suitable trees available within limits.

From this point, the ¼ sec. cor. of secs. 31 and 32, bears S. 0° 06' W., 39.88 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

¼
S 31 | S 32
T 23 S R 4 W
1963

from which the remains of the original bearing trees

A root hole, bears N. 55° E., 51 lks. dist.

A root hole, bears S. 56° W., 40 lks. dist.

and bearing trees mkd. by White.