

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: right;">S 1/16 S 30 S 29 1976</p> <p style="text-align: right;">Found ok by Carl Sweeden 2/4/2003 C.S. File 65/45-3</p>
	<p>from which</p> <p>A fir, 10 ins. diam., bears S. 27° E., 33½ lks. dist., mkd. S 1/16 S29 BT.</p> <p>A fir, 9 ins. diam., bears S. 56° W., 38½ lks. dist., mkd. S 1/16 S30 BT.</p> <p>Ascend 145 ft. over SE. slope.</p>
38.10	Top of ascent, slopes E.; desc. 5 ft. over NE. slope.
39.88	The ¼ sec. cor. of secs. 29 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">¼ S 30 S 29 T. 23 S R 4 W 1963</p>
	<p>from which the remains of bearing trees mkd. by Arthur Boyer, Deputy County Surveyor, in 1943</p> <p>A root hole, bears S. 55° E., 26 lks. dist., with a down cedar alongside, 12 ins. diam., no marks visible on decayed blaze.</p> <p>A root hole, bears N. 10° W., 5 lks. dist., with a turned out fir stump alongside, 30 ins. diam., with healed blaze.</p> <p>and the remains of bearing trees mkd. by White and Beck, in 1963</p> <p>A sawed fir stump, 34 ins. diam., bears N. 72° E., 96 lks. dist., with scribe marks ¼ S29 BT visible on open blaze.</p> <p>A sawed fir stump, 48 ins. diam., bears N. 31½° W., 101 lks. dist., with scribe marks ¼ S30 BT visible on open blaze.</p> <p>and new bearing trees</p> <p>A madrone, 7 ins. diam., bears N. 87½° E., 63 lks. dist., mkd. ¼ S29 BT.</p> <p>A madrone, 8 ins. diam., bears S. 30½° W., 52 lks. dist., mkd. ¼ S30 BT.</p>
	<p>N. 0° 06' W., beginning new measurement.</p> <p>Descend 15 ft. over NE. slope.</p>
14.45	Creek, 1 lk. wide, course S. 30° E.; asc. 100 ft. over S. slope.
20.135	Point for the N 1/16 sec. cor. of secs. 29 and 30.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>