

Dependant Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">N 1/16 S 30 S 29 1976</p>
	<p>from which</p> <p>A cedar, 8 ins. diam., bears N. 57° E., 31 lks. dist., mkd. N 1/16 S29 BT.</p> <p>A fir, 14 ins. diam., bears S. 36½° W., 39½ lks. dist., mkd. N 1/16 S30 BT.</p> <p>Ascend 45 ft. over S. slope.</p>
24.85	Ridge, bears E. and W.; desc. 50 ft. over NE. slope.
37.00	Bottom of descent, slopes SE.; asc. 20 ft. over S. slope.
40.27	<p>The cor. of secs. 19, 20, 29, and 30, determined at record distance from the remains of the original bearing trees:</p> <p>A fir snag, 43 ins. diam., bears N. 58½° E., 28 lks. dist., with chaining notch visible on opened blaze. (Record, N. 55° E.)</p> <p>A sawed fir stump, 18 ins. diam., bears S. 19° E., 34 lks. dist., with scribe marks S29 visible on open blaze. (Record, S. 25° E.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W S 19 S 20 S 30 S 29 1976</p> <p>from which new bearing trees</p> <p>A fir, 8 ins. diam., bears N. 71¾° E., 68 lks. dist., mkd. T23S R4W S20 BT.</p> <p>A fir, 6 ins. diam., bears S. 19° E., 57 lks. dist., mkd. T23S R4W S29 BT.</p> <p>A fir, 8 ins. diam., bears S. 7° W., 193½ lks. dist., mkd. T23S R4W S30 BT.</p> <p>A fir, 16 ins. diam., bears N. 51½° W., 39½ lks. dist., mkd. T23S R4W S19 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, madrone, myrtle, maple, oak, chinquapin, and dogwood; undergrowth, salal, hazel, vine maple, poison oak, rhododendron, Oregon grape, and fern.</p>
	<p>From the ¼ sec. cor. of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p>