

16162

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

$\frac{1}{4}$ $\frac{S\ 20}{S\ 29}$
T 23 S R 4 W
1963

from which the remains of bearing trees mkd. by White and Beck, in 1963

A sawed fir stump, 48 ins. diam., bears N. 67° W., 96 lks. dist., with scribe marks $\frac{1}{4}$ S20 BT visible on open blaze.

A sawed cedar stump, 30 ins. diam., bears S. 68° W., 76 lks. dist., with scribe marks $\frac{1}{4}$ S29 BT visible on open blaze.

and new bearing trees

A grand fir, 10 ins. diam., bears N. 58° W., 110 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S20 BT.

A fir, 4 ins. diam., bears S. 1 $\frac{1}{2}$ ° W., 51 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

N. 89° 16' W., bet. secs. 20 and 29.

Ascend 450 ft. over SE. slope, through scattered timber and dense undergrowth.

14.10 Ridge, bears N. 15° E. and S. 5° W.; desc. 105 ft. over SW. slope.

19.82 Point for the W 1/16 sec. cor. of secs. 20 and 29.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 20}{S\ 29}$
1976

from which

A fir, 5 ins. diam., bears N. 44° W., 141 lks. dist., mkd. W 1/16 S20 BT.

A sandstone boulder, 4 x 4 x 2 ft. above ground, bears S. 28° E., 95 lks. dist., mkd. X80 on top.

Descend 70 ft. over SW. slope.

38.15 Creek, 1 lk. wide, course S.; asc. 20 ft. over SE. slope.

39.64 The cor. of secs. 19, 20, 29, and 30.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, oak, maple, myrtle, alder, and chinquapin; undergrowth, salal, rhododendron, Oregon grape, vine maple, poison oak, hazel, and fern.

From the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, perpetuated by person(s) unknown, monumented with an iron rod, 1 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of the original bearing trees: