

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
S 19 | S 20  
T 23 S R 4 W  
1976

from which new bearing trees

A fir, 7 ins. diam., bears N.  $35\frac{1}{2}^{\circ}$  E., 27 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

A fir, 8 ins. diam., bears N.  $35\frac{1}{2}^{\circ}$  W., 26 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

Reset "T" shaped iron rod alongside iron post.

N.  $1^{\circ} 35'$  W., bet. secs. 19 and 20.

Descend 85 ft. over NW. slope, through heavy timber and dense undergrowth.

- 3.85 Dirt road, 30 lks. wide, bears N.  $55^{\circ}$  W. and S.  $35^{\circ}$  E.
- 6.05 Creek, 5 lks. wide, course N.  $35^{\circ}$  W., curving to N.; asc. 70 ft. over SW. slope.
- 6.70 Dirt road, 30 lks. wide, bears N.  $60^{\circ}$  E. and S.  $70^{\circ}$  W.
- 12.10 Dirt road, 30 lks. wide, bears N.  $80^{\circ}$  W. and S.  $45^{\circ}$  E.
- 22.20 Ridge, bears N.  $70^{\circ}$  W. and S.  $80^{\circ}$  E.; desc. 105 ft. over NW. slope.
- 37.70 Adams Creek, 5 lks. wide, course N.  $80^{\circ}$  W.; asc. 35 ft. over SW. slope.
- 40.43 The cor. of secs. 17, 18, 19, and 20, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, and further perpetuated by Vernon Tracy, Deputy County Surveyor, in 1965, monumented with an axle,  $1\frac{3}{4}$  ins. diam., firmly set, projecting 12 ins. above ground, from which the remains of the original bearing trees:
- A sawed fir stump, 44 ins. diam., bears N.  $47^{\circ}$  E., 83 lks. dist., rescribed by Byron, in 1959, with scribe marks T23S R4W S17 CS BT visible on open blaze. (Record, N.  $42^{\circ}$  E.)
- A fir snag, 18 ins. diam., bears S.  $69\frac{1}{2}^{\circ}$  E., 73 lks. dist., rescribed by Byron, in 1959, with scribe marks T23S R4W S20 CS BT visible on open blaze. (Record, S.  $71^{\circ}$  E., 71 lks.)
- A sawed fir stump, 42 ins. diam., bears S.  $59^{\circ}$  W., 38 lks. dist., no marks visible.
- A fir, 22 ins. diam., bears N.  $69^{\circ}$  W., 47 lks. dist., rescribed by Byron, in 1959, with scribe marks T23S W S visible on bark blaze.

and bearing trees mkd. by Tracy