

T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

Corrective Dependent Resurvey of a Portion of
the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the survey by Samuel C. Flint,
U. S. Deputy Surveyor, in 1882,
the survey by Charles E. Roberts,
U. S. Deputy Surveyor, in 1905-1907,
and correcting the resurvey by Harold D. Corbin,
Cadastral Surveyor, in 1957)

Beginning at the cor. of secs. 2, 3, 10, and 11, monu-
mented with an iron post, 2½ ins. diam., firmly set,
projecting 4 ins. above ground, with brass cap mkd.

T 27 S R 2 W
S 3 | S 2
S 10 | S 11
1957

from which the remains of the original bearing trees

A sawed fir stump, 36 ins. diam., bears N. 19° E.,
83 lks. dist., with healed blaze.

A sawed fir stump, 32 ins. diam., bears S. 50° E.,
94 lks. dist., no marks visible.

A cedar, 25 ins. diam., bears N. 59° W., 75 lks.
dist., with fragmentary scribe marks visible
on open blaze.

and the remains of bearing trees mkd. by Corbin

A fir, 10 ins. diam., bears N. 60° E., 87 lks.
dist., with healed blaze.

A cedar, 12 ins. diam., bears S. 28½° E., 30 lks.
dist., with healed blaze.

A sugar pine snag, 5 ins. diam., bears S. 27° W.,
28 lks. dist., with fragmentary scribe marks
visible on open blaze.

A hemlock, 12 ins. diam., bears N. 57½° W., 33
lks. dist., with healed blaze. (Record, fir)

and a bearing tree mkd. by James W. Byron, Deputy County
Surveyor, in 1960

A hemlock, 12 ins. diam., bears N. 21½° W., 45
lks. dist., with healed blaze.

S. 89° 02' W., along south boundary of sec. 3, marking
and blazing the true line.

Ascend 120 ft. over NE. slope, through heavy timber and
dense undergrowth.

13.60 Spur, slopes N. 45° W.; desc. 155 ft. over NW. slope.

24.15 Ravine, drains N.; desc. 95 ft. over NW. slope.