

16173

Corrective Dependent Resurvey of a Portion of
the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS
39.91

The $\frac{1}{4}$ sec. cor. of sec. 10 only, on the S. bdy. of sec. 3, established by Romanso Ware, Registered Land Surveyor No. 1005, in 1978; monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd.

T 27 S R 2 W

$\frac{1}{4}$ S 10

RLS No. 1005
1978

from which a bearing tree mkd. by Ware

A white fir, 13 ins. diam., bears S. 85° W., 69 lks. dist., with scribe marks $\frac{1}{4}$ S10 BT visible on open blaze.

From this point, a corner established by Thomas E. Shrum, Jr., Registered Engineer No. 4287, in 1965, bears S. 14° E., 0.110 chs. dist., monumented with an iron post, $\frac{3}{8}$ in. diam., firmly set, projecting 10 ins. above ground, with aluminum cap mkd.

USP CO. PROPERTY

T 27 S $\frac{1}{4}$ cor
R 2 W

Sec 10
RE 4287
1965

from which a bearing tree mkd. by Shrum

A hemlock, 8 ins. diam., bears S. 8° E., $57\frac{1}{2}$ lks. dist., with scribe marks S10 N $\frac{1}{4}$ BT visible on open blaze.

Descend 5 ft. over NW. slope.

40.42

Point for the $\frac{1}{4}$ sec. cor. of sec. 3 only, determined by the method of broken boundaries; there is no remaining evidence of the original corner.

From this point, the $\frac{1}{4}$ sec. cor. of sec. 3 only, erroneously positioned by Corbin, in 1957, and rehabilitated by Vernon R. Tracy, Deputy County Surveyor, in 1968, bears N. $15^\circ 15'$ W., 0.260 chs. dist., monumented with an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., firmly set, 22 ins. in the ground, mkd. and witnessed as described in the official record.

I remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 S R 2 W

$\frac{1}{4}$ S 3

1978
1957

from which the remaining bearing tree mkd. by Corbin and rescribed by Tracy

A fir, 15 ins. diam., bears N. $42\frac{3}{4}^\circ$ W., $61\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S3 CS BT visible on open blaze.