

16173  
16175

Corrective Dependent Resurvey of a Portion of  
the Subdivisional Lines,  
T. 27 S., R. 2 W., Willamette Meridian, Oregon

255

CHAINS	
31.00	Paved road, 40 lks. wide, bears N. 25° E. and S. 25° W.
33.10	Gravelled road, 20 lks. wide, bears N. 25° E. and S. 25° W.
39.40	Point for the closing cor. of secs. 9 and 10, hereinafter described.
	Thence over gentle SE. slope.
40.47	The cor. of secs. 3 and 4 only, perpetuated and recorded by Dennis Gaylord, Deputy County Surveyor, in 1977, monumented with an iron post, 1½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T 27 S R 2 W FO. OIK BY N. HIBBS S 4   S 3 JULY 2003, M 142-51 S 9 1977</p> <p><i>FD OK D. EDWARDS 3/2001 M136-69 CS65B4-5</i></p>
	from which the remains of bearing trees mkd. by Roberts
	A fir root crown, size indeterminate, bears N. 31° E., 48 lks. dist.
	A sawed fir stump, 26 ins. diam., bears N. 51½° W., 141 lks. dist., with scribe marks S R2W visible on open blaze.
	and bearing trees mkd. by Corbin
	A fir, 10 ins. diam., bears N. 24° E., 70½ lks. dist., with healed blaze.
	A cedar, 15 ins. diam., bears N. 25° W., 123 lks. dist., with healed blaze.
	From this point, the cor. of secs. 3 and 4 only, erroneously positioned by Corbin, in 1957, bears N. 43° W., 0.225 chs. dist., monumented with an iron post, 28 ins. long, 2½ ins. diam., firmly set 26 ins. in the ground, mkd. and witnessed as described in the official record.
	I remove the iron post.
	From this same point, a point established by Robert G. Lecklider, Registered Engineer No. 4079, in 1959, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above ground, bears N. 22° E., 0.025 chs. dist.
	Land, mountainous.
	Soil, rocky clay.
	Timber, fir, hemlock, cedar, maple, oak, madrone, and alder; undergrowth, salal, poison oak, vine maple, and fern.
	From the ¼ sec. cor. of secs. 9 and 10, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, and further perpetuated by Romano Ware, Registered Land Surveyor No. 1005, in 1978, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.