

Corrective Dependent Resurvey of a Portion of
the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

From this point, the S 1/16 sec. cor. of secs. 3 and 4, erroneously positioned by Corbin, in 1957, bears N. 54° 11' W., 0.150 chs. dist., monumented with an iron post, 28 ins. long, 2½ ins. diam., firmly set 22 ins. in the ground, mkd. and witnessed as described in the official record.

I remove the iron post, and at the corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 4 | S 3
1978
1957

from which the remaining bearing tree mkd. by Corbin

A hemlock, 12 ins. diam., bears N. 85° E., 51 lks. dist., with fragmentary scribe marks visible on open blaze.

and a new bearing tree

A hemlock, 6 ins. diam., bears N. 32° W., 5 lks. dist., mkd. S 1/16 S4 BT.

Ascend 150 ft. over S. slope.

28.00 Spur, slopes S. 45° E.; desc. 85 ft. over NE. slope.

29.70 Creek, 5 lks. wide, course S. 45° E.; asc. 260 ft. over S. slope.

44.24 The ¼ sec. cor. of secs. 3 and 4, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 27 S R 2 W
¼
S 4 | S 3
1957

from which the remains of the original bearing trees

A fir, 28 ins. diam., bears S. 28° E., 19 lks. dist., with healed lower blaze and fragmentary scribe marks visible on upper bark blaze.

A sawed fir stump, 42 ins. diam., bears N. 35° W., 65 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Corbin

A fir, 14 ins. diam., bears N. 52° E., 43 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 13 ins. diam., bears S. 81° W., 48 lks. dist., with healed blaze.

Land, mountainous.
Soil, rocky clay.

FD
OK
D. Edwards
4/2001
M 126-69
CS 65/345