

Dependent Resurvey of a Portion of the South Boundary,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A live oak, 13 ins. diam., bears S. 78° E., 61 lks. dist., with scribe marks S 6 visible on opened blaze.

A fir stump, size indeterminate, bears N. 38° W., 97 lks. dist., no marks visible.

and bearing trees mkd. by Byron

A live oak, 8 ins. diam., bears N. 49° E., 70 lks. dist., with scribe marks T31S R7W S31 CS BT visible on open blaze.

A fir, 14 ins. diam., bears S. 48½° E., 37 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 69° W., 49 lks. dist., with healed blaze.

A live oak, 6 ins. diam., bears N. 41° W., 7 lks. dist., with scribe marks S36 CS BT visible on partially open blaze.

N. 89° 51' W., bet. secs. 1 and 36, marking and blazing the true line.

Descend 150 ft. over steep SW. slope, through heavy timber and dense undergrowth.

4.00 Creek, 3 lks. wide, course S. 20° E.; asc. 210 ft. over SE. slope.

10.75 Spur, slopes S. 20° E.; desc. 200 ft. over steep SW. slope.

16.60 Creek, 2 lks. wide, course S.; asc. 390 ft. over broken SE. slope.

29.00 Spur, slopes S. 40° E.; desc. 80 ft. over broken SW. slope.

38.21 Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 8 W
 S 36
 ¼ S 1
 T 32 S
 1977

from which

A fir, 6 ins. diam., bears N. 69½° E., 37½ lks. dist., mkd. ¼ S36 BT.

A fir, 8 ins. diam., bears S. 17½° W., 59 lks. dist., mkd. ¼ S1 BT.

Descend 45 ft. over broken SW. slope.

43.65 Ravine, drains S. 40° E.; asc. 760 ft. over broken SE. slope.