

16186

Dependent Resurvey of a Portion of the South Boundary,  
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 32 ins. diam., bears N. 82° E., 51 lks.  
dist., with healed blaze. (Record, 57 lks.)

A fir, 25 ins. diam., bears S. 65° E., 41 lks.  
dist., with healed blaze.

A fir, 44 ins. diam., bears S. 28° W., 30 lks.  
dist., with scribe marks T31S R8W S3 BT visible  
on bark blaze. This tree was rescribed by Byron,  
with scribe marks CS 3 R8W S3 C BT visible on  
open blaze.

A fir, 35 ins. diam., bears N. 35° W., 42 lks.  
dist., with scribe marks R8 visible on bark  
blaze. This tree was rescribed by Byron, with  
fragmentary scribe marks visible on partially  
open blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, live oak, myrtle,  
chinquapin, and alder; undergrowth, salal, poison oak,  
Oregon grape, rhododendron, vine maple, and fern.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the Survey by William H. Byars,  
U. S. Deputy Surveyor, in 1882-83,  
and the resurvey and remonumentation by  
C. Albert White, Harold D. Corbin, and Donald R. Beck,  
Cadastral Surveyors, in 1960-62)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy.  
of the Tp.

N. 1° 34' E., bet. secs. 35 and 36, marking and blazing  
the true line.

Ascend 350 ft. over SW. slope, through heavy timber and  
dense undergrowth.

20.05 Spur, slopes W.; desc. 270 ft. over NW. slope.

40.25 The  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, determined at record  
bearing and distance from the original bearing trees:

A cedar, 40 ins. diam., bears S. 70° E., 18 lks.  
dist., no marks visible. (Record, pine)

A fir, 26 ins. diam., bears S. 75° W., 8 lks.  
dist., no marks visible on chopped open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 31 S R 8 W

S 35 | S 36

1977

from which new bearing trees