

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 33 ins. diam., bears S. $50\frac{1}{2}^{\circ}$ E., 22 lks.
dist., mkd. $\frac{1}{4}$ S36 BT.

A fir, 26 ins. diam., bears S. $88\frac{1}{2}^{\circ}$ W., 14 lks.
dist., mkd. $\frac{1}{4}$ S35 BT.

N. $0^{\circ} 09'$ E., beginning new measurement.

Descend 135 ft. over NW. slope.

6.25 Ravine, drains S. 80° W.; asc. 145 ft. over SW. slope.

11.55 Spur, slopes W.; desc. 130 ft. over NW. slope.

19.25 Ravine, drains N. 75° W.; asc. 25 ft. over SW. slope.

23.15 Spur, slopes W.; desc. 70 ft. over NW. slope.

26.20 Ravine, drains N. 80° W.; asc. 175 ft. over SW. slope.

34.75 Spur, slopes W.; desc. 110 ft. over NW. slope.

38.86 Point for the cor. of secs. 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 8 W			
S 26		S 25	
S 35		S 36	
1977			

from which

A madrone, 15 ins. diam., bears N. $5\frac{1}{2}^{\circ}$ E., 32 lks.
dist., mkd. T31S R8W S25 BT.

A fir, 18 ins. diam., bears S. $80\frac{1}{2}^{\circ}$ E., $21\frac{1}{2}$ lks.
dist., mkd. T31S R8W S36 BT.

A fir, 16 ins. diam., bears S. $6\frac{1}{2}^{\circ}$ W., 114 lks.
dist., mkd. T31S R8W S35 BT.

A fir, 14 ins. diam., bears N. $54\frac{1}{4}^{\circ}$ W., $74\frac{1}{2}$ lks.
dist., mkd. T31S R8W S26 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, madrone, myrtle, and chinquapin; undergrowth, salal, Oregon grape, poison oak, rhododendron, vine maple, and fern.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., perpetuated and recorded by James W. Byron, County Surveyor, in 1970, monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S			
R S 25		S 30	R
8 S 36		S 31	7
W			W
1970			