

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A ponderosa pine snag, 47 ins. diam., bears
S. 68° E., 122 lks. dist., with fragmentary
scribe marks visible on decayed blaze.

A ponderosa pine, 53 ins. diam., bears S. 53½° W.,
250 lks. dist., with healed blaze. (Record,
S. 62° W.)

and bearing trees mkd. by Byron

A fir, 13 ins. diam., bears N. 24° E., 34 lks.
dist., with fragmentary scribe marks visible
on decayed blaze.

A fir, 20 ins. diam., bears S. 27° E., 27 lks.
dist., with fragmentary scribe marks visible
on partially open blaze.

A fir, 17 ins. diam., bears S. 59° W., 33 lks.
dist., with fragmentary scribe marks visible
on partially open blaze.

A fir, 15 ins. diam., bears N. 19° W., 34 lks.
dist., with fragmentary scribe marks visible
on partially open blaze.

S. 86° 49' W., bet. secs. 25 and 36.

Ascend 20 ft. over SE. slope, through heavy timber and
dense undergrowth.

- 3.65 Spur, slopes SE.; desc. 5 ft. over SW. slope.
- 7.70 Spur, slopes SW.; desc. 265 ft. over SW. slope.
- 11.30 Gravelled road, 25 lks. wide, bears N. 45° W. and
S. 45° E.
- 17.05 Spur, slopes SW.; desc. 40 ft. over SW. slope.
- 18.55 Head of ravine, drains S.; asc. 15 ft. over SE. slope.
- 19.90 Spur, slopes SW.; desc. 10 ft. over SW. slope.
- 21.45 Ravine, drains SE.; asc. 265 ft. over E. slope.
- 28.80 Top of ascent, slopes S.; desc. 20 ft. over SW. slope.
- 32.60 Ravine, drains S.; asc. 145 ft. over SE. slope.
- 35.85 Gravelled road, 25 lks. wide, bears N. and S.
- 36.39 The ¼ sec. cor. of secs. 25 and 36, perpetuated and re-
corded by James W. Byron, County Surveyor, in 1967, monu-
mented with an iron post, 1¼ ins. diam., firmly set,
projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

¼ $\frac{S\ 25}{S\ 36}$
1967

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears
N. 60° W., 119 lks. dist., no marks visible.