

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A cedar, 57 ins. diam., bears S. 60° W., 62 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partially open blaze. (Record, 56 lks.)

and bearing trees mkd. by Byron

A fir, 18 ins. diam., bears N. 17° E., 66 $\frac{1}{2}$ lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 50° W., 29 lks. dist., with healed blaze.

S. 89° 45' W., beginning new measurement.

Ascend 80 ft. over E. slope.

3.20 Ridge, bears N. and S.; desc. 315 ft. over W. slope.

17.95 Bottom of descent, slopes N.; asc. 5 ft. over E. slope.

19.60 Ridge, bears N. and S.; desc. 435 ft. over NW. slope.

39.06 The cor. of secs. 25, 26, 35, and 36.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, myrtle, and chinquapin; undergrowth, salal, vine maple, poison oak, Oregon grape, rhododendron, and fern.

N. 0° 53' W., bet. secs. 25 and 26.

Descend 615 ft. over N. slope, through heavy timber and dense undergrowth.

18.00 Creek, 1 lk. wide, course N. 45° W.; asc. 115 ft. over SW. slope.

25.50 Spur, slopes N. 30° W.; desc. 155 ft. over NW. slope.

29.75 Creek, 1 lk. wide, course N. 55° W.; asc. 115 ft. over SW. slope.

35.00 Spur, slopes W.; desc. 140 ft. over NW. slope.

38.86 The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with the original basalt stone, 15 x 12 x 10 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 31 S R 8 W

$\frac{1}{4}$

S 26 | S 25

1977

from which

A fir, 16 ins. diam., bears N. 19 $\frac{1}{2}$ ° E., 61 lks. dist., mkd. $\frac{1}{4}$ S25 BT.