

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 24 ins. diam., bears S. 65° E., 12 lks. dist., with fragmentary scribe marks visible on bark blaze and healed blaze alongside.

A fir, 48 ins. diam., bears S. 45° W., 60 lks. dist., with fragmentary scribe marks visible on bark blaze.

A fir, 28 ins. diam., bears N. 42° W., 20 lks. dist., with fragmentary scribe marks visible on bark blaze.

S. 85° 11' W., bet. secs. 24 and 25.

Ascend 85 ft. over NE. slope, through heavy timber and dense undergrowth.

3.70 Ridge, bears N. 40° W. and S. 40° E.; desc. 530 ft. over NW. slope.

16.40 Creek, 3 lks. wide, course N. 20° W.; asc. 295 ft. over SW. slope.

23.15 Spur, slopes N. 25° E.; desc. 170 ft. over SW. slope.

30.00 Ravine, drains NW.; asc. 30 ft. over NE. slope.

31.15 Spur, slopes N. 55° W.; desc. 70 ft. over NW. slope.

35.70 Ravine, drains N. 30° W.; asc. 5 ft. over NE. slope.

38.45 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 8 W

$\frac{1}{4}$ $\frac{S\ 24}{S\ 25}$

1977

from which

A fir, 5 ins. diam., bears N. 45° E., 15 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

A fir, 8 ins. diam., bears S. 56 $\frac{1}{4}$ ° E., 44 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

Corner is located at top of ascent, slopes N.; desc. 225 ft. over NW. slope.

43.60 Spur, slopes N. 10° E.; desc. 80 ft. over NW. slope.

46.10 Creek, 3 lks. wide, course N.; asc. 265 ft. over NE. slope.

51.50 Spur, slopes N.; desc. 240 ft. over broken NW. slope.

76.90 The cor. of secs. 23, 24, 25, and 26.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, myrtle, and chinquapin; undergrowth, salal, hazel, poison oak, vine maple, rhododendron, Oregon grape, and fern.