

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	N. 1° 11' W., bet. secs. 23 and 24.
	Descend 230 ft. over NW. slope, through heavy timber and dense undergrowth.
4.60	Cow Creek Road, asphalt surfaced, 40 lks. wide, bears E. and W.
6.60	Cow Creek, 120 lks. wide, course N. 60° E.; asc. 420 ft. over SE. slope.
7.80	Southern Pacific Railroad, bears N. 50° E. and S. 50° W.
22.10	Ravine, drains S. 25° E.; asc. 585 ft. over SW. slope.
41.27	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 31 S R 8 W $\frac{1}{4}$ S 23   S 24 1977
	from which
	A fir, 6 ins. diam., bears N. 77 $\frac{1}{2}$ ° E., 14 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	A fir, 6 ins. diam., bears N. 89° W., 8 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	Ascend 2 ft. over SE. slope.
43.45	Ridge, bears N. 65° W. and S. 65° E.; desc. 100 ft. over NE. slope.
46.10	Ravine, drains N. 65° E.; desc. 95 ft. over NE. slope.
50.85	Creek, 3 lks. wide, course N. 55° E.; desc. 75 ft. over NE. slope.
58.15	Creek, 2 lks. wide, course N. 65° E.; desc. 5 ft. over NE. slope.
60.30	Creek, 4 lks. wide, course S. 70° E.; asc. 650 ft. over SE. slope.
82.54	Point for the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 31 S R 8 W S 14   S 13 S 23   S 24 1977
	from which
	A fir, 17 ins. diam., bears N. 18 $\frac{1}{2}$ ° E., 36 lks. dist., mkd. T31S R8W S13 BT.