

16194

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A madrone, 4 ins. diam., bears N. 60° W., 5 lks. dist., with fragmentary scribe marks visible on open blaze.

From this point, a cor. established by Dennis Crowe, Registered Land Surveyor No. 845, in 1972, bears S. 4° 24' W., 0.72 chs. dist., monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.

	T 31 S		
LS	S 13 S 18		
8	S 24 S 19		
4	1972		
5			

from which bearing trees mkd. by Crowe

A fir, 10 ins. diam., bears N. 70° E., 29 lks. dist., with healed blaze.

A pine, 10 ins. diam., bears S. 22° E., 31 lks. dist., with healed blaze.

From this same point, the ¼ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., bears N. 0° 29' W., 39.87 chs. dist., perpetuated and recorded by James W. Byron, County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

	T 31 S		
R	S S		R
8 ¼	13 18		7
W	1966		W

from which the remains of the original bearing trees

A fir root crown, bears S. 58° E., 65 lks. dist., no marks visible. (Record, 70 lks.)

A fir, 40 ins. diam., bears S. 46¼° W., 28 lks. dist., with healed blaze. (Record, S. 42° W.)

and bearing trees mkd. by Byron

A live oak, 10 ins. diam., bears N. 6¼° E., 9 lks. dist., with scribe marks ¼ S18 CS BT visible on open blaze.

A live oak, 8 ins. diam., bears S. ½° W., 31 lks. dist., with scribe marks ¼ 13 CS BT visible on open blaze.

From this same point, the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., bears S. 0° 29' E., 79.74 chs. dist., hereinbefore described.

These control lines were fully retraced and search was made for intervening corners, none of which were recovered.

S. 87° 21' W., bet. secs. 13 and 24.

Descend 165 ft. over SW. slope, through heavy timber and dense undergrowth.