

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS 7.95	Ravine, drains S.; asc. 130 ft. over SE. slope.
24.00	Ravine, drains S.; asc. 380 ft. over broken SE. slope.
38.91	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 31 S R 8 W $\frac{1}{4}$ $\frac{S 13}{S 24}$ 1977 </div> from which A fir, 9 ins. diam., bears N. $6\frac{1}{2}^{\circ}$ E., $58\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S13 BT. A madrone, 8 ins. diam., bears S. 72° E., $24\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S24 BT. Ascend 665 ft. over E. slope.
65.20	Ridge, bears N. and S.; desc. 50 ft. over SW. slope.
77.82	The cor. of secs. 13, 14, 23, and 24. Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, myrtle, oak, live oak, alder, and chinquapin; undergrowth, salal, hazel, vine maple, rhododendron, poison oak, Oregon grape, and fern.
	N. $0^{\circ} 05'$ W., bet. secs. 13 and 14. Ascend 330 ft. over SW. slope, through heavy timber and dense undergrowth.
10.60	Ridge, bears E. and W.; desc. 190 ft. over NE. slope.
20.60	From this point, a cor. established by Dennis Crowe, Registered Land Surveyor No. 845, in 1973, bears East, 0.07 chs. dist., monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. <div style="text-align: center;"> S $\frac{1}{16}$ S 14 S 13 1973 </div> from which bearing trees mkd. by Crowe A white fir, 16 ins. diam., bears N. 9° E., $33\frac{1}{2}$ lks. dist., with healed blaze. A white fir, 18 ins. diam., bears East, 37 lks. dist., with healed blaze. Descend 240 ft. over broken NE. slope.