

267

16210

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Beginning at the cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by the Douglas County Surveyor, in 1970, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS

T 23 S R 9 W

S 28 | S 27

S 33 | S 34

1970

OFFICE

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N. 52½° E., 63 lks. dist., no marks visible.

A hemlock snag, 28 ins. diam., bears S. 82° E., 38 lks. dist., with scribe marks TS visible on bark.

and bearing trees mkd. by the Douglas County Surveyor

A fir, 10 ins. diam., bears N. 40° E., 33 lks. dist., with healed blaze.

A hemlock, 12 ins. diam., bears N. 76° W., 57½ lks. dist., with healed blaze.

No other suitable trees available within limits.

N. 3° 13' E., bet. secs. 27 and 28, marking and blazing the true line.

Descend 830 ft. over NW. slope, through heavy young timber and dense undergrowth.

39.08

Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 9 W

S 28 | S 27

1977

from which

A hemlock, 17 ins. diam., bears N. 47½° E., 35½ lks. dist., mkd. ¼ S27 BT.

A hemlock, 3 ins. diam., bears N. 68¾° W., 9 lks. dist., mkd. X BT.

Descend 555 ft. over broken NW. slope.

62.40

Creek, 2 lks. wide, course N. 50° W.; asc. 130 ft. over SW. slope, also enter heavy timber, edge bears E. and W.

67.55

Spur, slopes N. 60° W.; desc. 40 ft. over NE. slope.

68.75

Ravine, drains N. 60° W.; asc. 55 ft. over SW. slope.

73.85

Spur, slopes W.; desc. 20 ft. over NW. slope.