

16211

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS  
76.15

Ravine, drains N. 50° W.; asc. 30 ft. over SW. slope.

78.16

The cor. of secs. 21, 22, 27, and 28, determined at record bearing and distance from the original bearing trees:

A fir, 35 ins. diam., bears N. 37° E., 32 lks. dist., with scribe marks T23S R9W S22 BT visible on bark blaze.

A fir, 63 ins. diam., bears S. 80° E., 38 lks. dist., with healed blaze.

A fir, 47 ins. diam., bears S. 0½° W., 122 lks. dist., with scribe marks T S W visible on weathered bark blaze.

A fir, 50 ins. diam., bears N. 77° W., 62 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 9 W
S 21   S 22
S 28   S 27
1977

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, chinquapin, and yew; undergrowth, rhododendron, hazel, huckleberry, willow, salmonberry, salal, Oregon grape, and fern.

From the SE. cor. of sec. 20 only, determined from the remains of an original bearing tree:

A decayed fir stump, 10 ins. diam., bears S. 18° W., 29 lks. dist., no marks visible.

and the remains of a bearing tree mkd. and recorded by H. T. Lewis, Registered Engineer No. 722, in 1933

A cedar snag, 10 ins. diam., bears N. 48° W., 41 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S
R 9 W
S 20   S 28
1977

from which a new bearing tree

A cedar, 11 ins. diam., bears N. 61½° W., 38 lks. dist., mkd. T23S R9W S20 BT.

No other suitable trees available within limits.

N. 0° 26' W., on the E. bdy. of sec. 20.