

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

- Ascend 25 ft. over SW. slope, through scattered timber and dense undergrowth.
- 4.80 True point for the closing cor. of secs. 21 and 28, hereinafter described.
- Ascend 140 ft. over SW. slope.
- 9.10 Spur, slopes N. 45° W.; desc. 290 ft. over NE. slope.
- 20.30 Gravelled road, 30 lks. wide, bears N. 70° W. and S. 70° E.
- 21.50 Slideout Creek, 10 lks. wide, course N. 80° W.; asc. 300 ft. over SW. slope.
- 23.10 Gravelled road, 30 lks. wide, bears N. 85° W. and S. 85° E.
- 36.75 Ridge, bears N. 70° W. and S. 70° E.; desc. 70 ft. over NW. slope.
- 39.57 Point for the $\frac{1}{4}$ sec. cor. of sec. 20 only, at midpoint latitudinally on the E. bdy. of sec. 20; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 23 S
R 9 W
 $\frac{1}{4}$ S 20
1977
- from which
- A hemlock, 20 ins. diam., bears S. $52\frac{1}{2}$ ° W., 75 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S20 BT.
- A hemlock, 13 ins. diam., bears N. $71\frac{1}{2}$ ° W., 38 $\frac{1}{2}$ lks. dist., mkd. X BT.
- Descend 180 ft. over NW. slope.
- 44.02 Point for the $\frac{1}{4}$ sec. cor. of sec. 21 only, at midpoint latitudinally on the W. bdy. of sec. 21.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 23 S
R 9 W
 $\frac{1}{4}$ S 21
1977
- from which
- A white fir, 27 ins. diam., bears N. 50° E., 110 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
- A fir, 9 ins. diam., bears S. $69\frac{3}{4}$ ° E., 18 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
- Descend 155 ft. over NW. slope.
- 47.30 Soup Creek Road, asphalt surfaced, 35 lks. wide, bears N. 55° E. and S. 70° W.