

16213

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAIN#
50.46

Soup Creek, 20 lks. wide, course N. 70° W.; asc. 125 ft. over SE. slope.

59.22

The N 1/16 sec. cor. of sec. 20 only, established and recorded by Arthur R. Evans, Registered Engineer No. 2741, in 1951, when the 1/4 sec. cor. of sec. 20 only was still in existence, determined from the remains of bearing trees mkd. by Evans:

A hemlock, 19 ins. diam., bears S. 60° W., 35 lks. dist., with scribe marks 20 visible on open blaze.

A maple snag, 18 ins. diam., bears N. 60° W., 39 lks. dist., with scribe marks 1/16 S visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16 |
S 20 |
1977

from which new bearing trees

A hemlock, 9 ins. diam., bears S. 43° W., 129 lks. dist., mkd. N 1/16 S20 BT.

A hemlock, 15 ins. diam., bears N. 64° W., 73 1/2 lks. dist., mkd. N 1/16 S20 BT.

N. 0° 06' W., beginning new measurement.

Ascend 360 ft. over broken SE. slope.

19.92

The cor. of secs. 16 and 20 only, on the W. bdy. of sec. 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 23 S R 9 W
S 16 | S 21
S 20 |
1969

from which the remains of the original bearing trees

A sawed fir stump, 27 ins. diam., bears N. 10° E., 33 lks. dist., no marks visible.

A sawed fir stump, 18 ins. diam., bears N. 81° W., 9 lks. dist., with scribe marks BT visible on open blaze. (Record, N. 70° W.)

and a bearing tree described by Jelley and Steward

A hemlock, 15 ins. diam., bears N. 87 1/2° E., 102 lks. dist., with scribe marks T23S R9W S21 BT visible on open blaze.

and bearing trees mkd. by Jelley and Steward

A hemlock, 12 ins. diam., bears N. 60 1/2° W., 95 1/2 lks. dist., with scribe marks S16 BT visible on partially healed blaze. (Record, 93 lks.)